



VpCI® ADDITIVES FOR WATER TREATMENT



Cooling Loop Gator® Patented VpCI® Tower Lay-up/Mothballing



PRODUCT DESCRIPTION

Cortec's Cooling Loop Gator is a Vapor phase Corrosion Inhibitor (VpCI) powder packaged in polyvinyl-alcohol (PVA) water-soluble bags. Developed for seasonal, short or long term lay-up, Cooling Loop Gator protects enclosed spaces for up to 12 months. Once the bag and powder dissolve, the VpCIs adsorb on all metal surfaces - reaching recessed areas and interior cavities. The VpCIs form a strong molecular layer on the metal that protects in both the liquid and vapor phase.

FEATURES

- Provides excellent corrosion protection during lay-up period
- Can be used as a corrosion inhibitor additive in the majority of water treatment programs
- Provides multimetal protection, including galvanized steel and yellow metals (copper, brass)
- Protects inaccessible and recessed surfaces
- Does not need to be removed prior to start up

- Eliminates environmental hazard and disposal problems
- Safe and easy to handle
- Biodegradable (>80%), non-toxic, and non-irritating
- Effective for wet lay-up and flushing applications
- Reduces chemical consumption and cost upon start up
- Easy to apply
- Increased worker productivity and safety
- Nitrite-, phosphate-, and chromate-free
- Compatible with the majority of commercially available biocides and antiscalants

METHOD OF APPLICATION

One Gator treats up to 250 gallons (0.95 m³) water. Remove and discard outer barrier bag. Add the water-soluble bags directly into cooling water. Recirculate treated water for about 10-12 hours to obtain good protective layer before shutdown. Either drain the water out (flushing lay-up) or leave treated water in cooling tower. After application, all internal surfaces should be covered or closed and valves shut off.

COMPATIBILITY

Cooling Loop Gator is compatible with most materials of construction in cooling towers (e.g. rubbers, polymers, etc.). Cooling Loop Gator is effective in the:

- Presence of non-oxidizing biocides
- Presence of oxidizing biocides*

Please consult a Cortec representative for further information before use with biocides.

*Keep free halogen concentration less than 2 ppm. When using a high concentration level of oxidizing biocides, consult Cortec about dosages.



DIMENSION

Bag 10" x 14" (25 cm x 35 cm)

PHYSICAL PROPERTIES OF POWDERAppearance White powder
pH 8.5-9.5 (1% aqueous)**PACKAGING AND STORAGE**

Cooling Loop Gator® is available in 4 x 2.2 lb (4 x 1 kg) bags per box. Store in sealed container in a dry and cool warehouse. Do not store in conditions above 150°F (66°C).

EPA/600/4-90/027F

Meets EPA requirements for discharge in freshwater in used concentration.

48-hour Static D. pulex and P. Promelas Toxicity test (fresh water):

EE#	Appendix	Sample ID	NOEC/LOEC, ppm	
			D. pulex	p.Prmelas
E-17766-01	A	Cooling Loop Gator®	10,000/> 10,000/>	10,000 10,000

CONDUCTIVITY CHART

Sample	Concentration	Conductivity with DI water	Conductivity with RO water
Gator	250 ppm	-139 μ S	-140 μ S
Gator	500 ppm	-259 μ S	-264 μ S
Gator	1000 ppm	-498 μ S	-500 μ S
DI water	N.A.	-3 μ S	N.A.
RO water	N.A.	N.A.	-6 μ S

FOR INDUSTRIAL USE ONLY**KEEP OUT OF REACH OF CHILDREN****KEEP CONTAINER TIGHTLY CLOSED****NOT FOR INTERNAL CONSUMPTION****CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION****LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet http://www.CortecVCI.com

printed on recycled paper  100% post consumer
Revised 12/5/12. ©Cortec Corporation 2000-2012. Supersedes: 6/22/07

©2012, Cortec®/Cooling Loop Gator®, and VpCI® are trademarks of Cortec Corporation. All Rights Reserved.
Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.
ISO accreditation applies to Cortec's process only.