



VpCI® EMITTING SYSTEMS & ELECTRONIC PRODUCTS

ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector



PRODUCT DESCRIPTION

ElectriCorr VpCI-239 is a multifunctional outdoor cleaner/corrosion protector. Its continuous Vapor phase Corrosion Inhibitor action saves money by extending product life and eliminating downtime due to corrosion. ElectriCorr VpCI-239 forms a very thin film proven effective against aggressive conditions including industrial, marine, and tropical regions. This film does not alter the electrical resistance or magnetic properties of metal substrates. ElectriCorr VpCI-239 can be safely applied for the corrosion protection of electronic circuits or relays without causing any significant changes in conductivity. ElectriCorr VpCI-239 can be safely used with most plastics, elastomers, and other non-metals. In addition to corrosion protection, ElectriCorr VpCI-239 is an excellent contact cleaner of oils, grime, and other contaminants.

ElectriCorr VpCI-239 is an effective outdoor inhibitor of galvanic corrosion for most metals and alloys normally found in electrical and electronic applications such as aluminum, copper, tin, and ferrous metals.

ElectriCorr VpCI-239 is free of CFCs and 1,1,1-Trichlorethane. Provides instant corrosion protection.

In severely corrosive environments, ElectriCorr VpCI-239 can be used along with Cortec's VpCI-100 series impregnated foam devices for extended continuous protection.

FEATURES

- Excellent outdoor protection
- Can be applied indoors
- Fast-drying, nonsticky corrosion inhibiting film
- Instant corrosion protection
- Long-term protection
- Minimized field service
- Increased corrosion protection at a lower cost than conventional rust preventives
- CFC and 1,1,1-Trichlorethane free
- Vapor phase protection in vented or unvented enclosures
- May be used as a cleaning agent
- Moisture-displacing and penetrating film characteristics
- Designed especially for protected outdoor electrical connections
- Outdoor equivalent of VpCI-238
- UV dye additive can be seen once the carrier has evaporated

TYPICAL APPLICATIONS

- Protects high or low voltage, and high or low current electrical and electronic devices such as relays, connectors, sensors, wiring, etc.
- Printed circuit boards
- Electrical contacts and components
- Electric motors
- Protects ferrous and non-ferrous metals
- Can be used in contact with engineering plastics, elastomers, and other non-metals
- Outdoor generators and junction boxes
- Spray for use after final assembly or in the field
- Outdoor and indoor electrical outlets



APPLICATION

Aerosol use:

Spray a very light mist over the area needing protection. Dry time is approximately 1-2 hours at 70°F and 50% relative humidity.

Note: Application of a heavy mist will result in a heavy film that sags and remains wet. More is not necessarily better and could cause fouling or other complications of electrical connections.

PACKAGING AND STORAGE

ElectriCorr VpCl-239 is available in:

1. 9.45 oz. (267.75 grams) aerosol spray (6 cans per carton)
2. 5 gallon (19 liter) pails
3. 55 gallon (208 liter) drums
4. Liquid totes and bulk

ElectriCorr VpCl-239 should be kept from high temperatures and in normal warehouse conditions to prevent from freezing. ElectriCorr VpCl-239 has a shelf-life of 3+ years in sealed packages.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE

INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 8/26/13. Cortec Corporation 2001-2013. Supersedes: 7/21/28.
ElectriCorr® is a trademark of Cortec Corporation © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.