



VpCI® Super Penetrant



PRODUCT DESCRIPTION

Cortec VpCI Super Penetrant offers a deep penetrating formulation that loosens frozen parts locked in rust. Its deep penetrating capabilities allow the user to go through as much as 1/2 inch (13 mm) of rust in 30 minutes. VpCI Super Penetrant can be applied by a variety of convenient methods to meet any application needs including brush, hand pump spray, aerosol, spray application, or dipping.

As VpCI Super Penetrant breaks through deep rust, it displaces moisture and water. Its superior surface wetting and moisture displacing properties allow it to spread rapidly and get underneath the moisture layer normally present on metal under atmospheric conditions. While loosening the rust, it lubricates metal so frozen parts can move freely. Utilizing patented Cortec VpCI technology, the VpCI Super Penetrant forms an ultra thin film on metal that offers 6 months of protection from corrosion in extreme conditions.

Cortec VpCI Super Penetrant can be used for indoor and outdoor applications. Its superior water displacing characteristics make it an ideal choice for applications of equipment and components that are exposed to outside weather. It also conforms to Federal Specifications for VV-P-216 Penetrating Oil for Loosening Frozen Metallic Parts and ASTM D-971 Test for Interfacial Tension of Oil against water.

FEATURES

- Provides universal corrosion protection for ferrous metals, galvanized steel, aluminum, brass, copper, babbitt, zinc, cadmium, and silver
- Loosens frozen and rusted metal parts making them easy to remove
- Meets the regulations set by California Air Resources Board for Volatile Organic Compounds in consumer products

TYPICAL APPLICATIONS

- Maintenance
- Lubrication
- Temporary storage - spray a light coating on flat metal before or after metalworking
- Small or complex metal parts - spray on or dip in
- General surface treatment - spray, dip, or brush surfaces to be protected for up to 24 months
- Home repairs of squeaky items

TYPICAL PROPERTIES

Appearance	Clear amber liquid
Film Type	Oily
Flash Point	170°F (77°C)
Removal Methods	Alkaline cleaners and solvents (VpCI-416/VpCI-419)
Density	6.8-7.0 lb/gal (0.82-0.84 kg/l)
Non-volatile Content	30-40%

PACKAGING AND STORAGE

VpCI Super Penetrant is packaged in 5 gallon (19 liter) pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. It is also available in aerosol form net weight 5.25oz (148.84g). The product should be stored sealed. Agitate before each use. Shelf life is up to 24 months.



PROTECTION PROPERTIES

VpCI Super Penetrant displaces water as effectively as a leading lubricating rust preventive (R.P.) oil while providing much better protection against corrosion.

Time Before Corrosion								
	Salt Spray (Days) ASTM B-117			Humidity Test (Days) ASTM D-1748				Water Dis- placing per MIL-C-83933
	Carbon Steel	Aluminum	Copper	Carbon Steel	Cast Iron	Aluminum	Copper	
VpCI Super Penetrant	5	15+	5	30+	10+	50+	50+	Pass
Leading Lubricating/ R.P. Oil	5	15+	3	30+	1	50+	50+	Pass

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE

INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
 Revised: 10/30/13. ©Cortec Corporation 2006-2013. All rights reserved. Supersedes: 5/31/13.
 © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form
 without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies
 to Cortec's processes only.