



HIGH PERFORMANCE VpCI PACKAGING

Cor-Pak[®] EX VpCI[®] Film



PRODUCT DESCRIPTION

Cor-Pak EX VpCI Film is made using high-density polyethylene and extruding with Vapor phase Corrosion Inhibitors (VpCI) to protect ferrous and most non-ferrous metals from corrosion. Simply wrap the metal object with Cor-Pak EX film. The VpCI in the film volatilizes and migrates with air then condenses on all metal surfaces, reaching all exposed and recessed areas.

Cor-Pak EX VpCI Film provides a high level of corrosion inhibitor protection along with the excellent moisture barrier properties of high-density polyethylene film. It is unaffected by most solvents, strong acids and alkalis.

Incorporating Cortec's proven Vapor phase Corrosion Inhibitors, Cor-Pak EX VpCI Film is the ideal solution when a combination of multimetal and mechanical protection is desired.

FEATURES

- Transparent
- Flexible
- Lightweight
- Strength & Conformability
- High Density Polyethylene Substrate
- Low Cost

BENEFITS

- Allows visual inspection without unwrapping
- Excellent for interleaving and wrapping
- Concentrated level of VpCI for maximum quick protection
- Priced to compete effectively with VpCI paper
- Easy-to-wrap product
- Low shipping costs
- Film will not tear or puncture when packaging oddly shaped parts
- Universal protection
- Protection against moisture superior to that offered by papers
- Reduces moisture and sulfur contamination found in VPI paper and corrugated containers
- Economical protection
- Extremely effective corrosion inhibitor protection
- Protects ferrous and most non-ferrous metals and alloys
- Environmentally friendly
- Good moisture barrier
- Recyclable

METALS PROTECTED

- Carbon steel
- Galvanized steel
- Stainless steel
- Copper and alloys
- Aluminum and aluminum alloys
- Brass
- Zinc

ADDITIONAL BENEFITS

- Highest performing VpCIs made
- Vapor phase inhibition protects inaccessible and recessed surfaces
- If VpCI layer is disturbed by opening the package, protection is restored by closing the package



CORTEC
CORPORATION

Environmentally Safe VCI/MCI[®] Technologies

- Protected parts can be used immediately without degreasing or cleaning
- No spraying, wiping, dipping, or surface preparation of metal required
- Convertible to a wide variety of sizes of shrouds and liners to protect small or large parts

THE APPLICATIONS

Cor-Pak EX VpCl Film provides corrosion protection to products, interleaved, wrapped or shrouded. It represents excellent economical and aesthetically pleasing replacements for VCI/VPI papers.

ADDITIONAL APPLICATIONS

- Parts and components
- Tools
- Bin and box liners
- Electrical motors and mechanical controls
- Electrical and electronic assemblies and components
- Interleaving of coils and sheets
- Foam-in-place applications
- Bearings
- Interleaving of trays for parts storage/handling

METHOD OF APPLICATIONS

When using Cor-Pak EX film, metal items should be completely wrapped or shrouded to prevent the entry of moisture or air.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

TYPICAL PROPERTIES

Form Extruded high-density polyethylene film
 Appearance Transparent film
 Thickness 1.0-1.25 mil (25-35 microns)

EXAMPLE

Barrier properties of various packaging materials

Materials	Grams of moisture transmitted per 24 hr. period	
	100 in ²	(cm ²)
Barrier Films	0.0	(0.000)
Cor-Pak EX film	0.5	(0.0008)
45 lb. Kraft PE Coated Paper	0.5	(0.0008)
1-mil Low-Density Polyethylene	0.9	(0.0014)
35 lb. Kraft Paper	Unlimited*	

*Will allow all moisture to pass through in a 24 hour period

PACKAGING AND STORAGE

Cor-Pak EX film is available in rolls and sheets in standard and custom sizes. Contact Cortec for minimum quantities and specific sizes.

This product should be stored indoors at ambient temperature, sealed with their original packaging. Under these conditions, shelf life is up to 24 months.

Note: When Cor-Pak EX film is used with petro-based coatings, there is a possibility of gel ink transfer.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet http://www.CortecVpCl.com

printed on recycled paper 10% post consumer
 Revised 4/22/03. ©Cortec Corporation 2002. All rights reserved. Supersedes: 12/20/02
 Cor-Pak® and VpCl® are trademarks of Cortec Corporation.

Distributed by:
ECORR Systems
 a Division of Root International, Inc.
 24650 State Road 54
 Lutz, FL 33559

sales@ecorrystems.com Tel: 866-830-4050
 www.ecorrystems.com Fax: 813-264-1975



Certificate No.70781

Certificate No.81867