



HIGH PERFORMANCE VpCI™ COATINGS

CorShield® VpCI™ Strippable Coating



PRODUCT DESCRIPTION

CorShield VpCI Strippable Coating is a water-based, non-flammable temporary coating that can be easily removed without the use of paint strippers or cleaners. The unique combination of water-based acrylic polymers, Vapor phase Corrosion Inhibitors (VpCI™s) and a thixotropic thickeners provides excellent barrier, surface and corrosion protection. CorShield VpCI Strippable Coating is ideally suited for use on bare metal, painted surfaces, and in applications where surface protection and corrosion inhibition are necessary.

Designed for use as a fast-drying, temporary coating for parts and equipment, CorShield VpCI Strippable Coating is resistant to sagging and running while remaining non-flammable and environmentally friendly. CorShield VpCI Strippable Coating is a clear coating that can be tinted in a variety of custom colors.

SUGGESTED USES

- Protection of clean metal surfaces for storage or shipment
- Protection of painted surfaces from physical damage during storage or shipping

- Paint booths
- Tooling
- Highly polished metal surfaces

FEATURES

- Does not leave residual contamination
- Water-based, non-flammable
- Near zero VOC, contains no co-solvent
- Prevents corrosion /oxidation of metals
- Provides multimetal protection
- Temporary coatings for any outdoor conditions
- Fast drying
- Nice smooth appearance
- Available in different colors
- Ease of application and clean-up
- Requires no solvent or paint removers
- Simple to dispose off as a solid waste

LIMITATIONS

Since strippability depends on application conditions and the type of surface to be protected, testing may be required prior to use.

- Use 2 coats on porous surfaces
- Use 2 coats for medium to long term outdoor protection

TYPICAL APPLICATION

CorShield VpCI Strippable Coating is supplied as a milky liquid which can be applied by spray, brush, roll or dip.

Applications include:

- Automotive body and frame
- Steel sheets
- Small parts
- Transit coatings

CorShield VpCI Strippable Coating can be used in one or two coats.

To achieve good strippability, the recommended thickness per coat should not be less than 2-mils (50 microns).



METALS PROTECTED

- Carbon steel
- Stainless steel
- Cast iron
- Aluminum and alloys

TYPICAL PROPERTIES

Appearance	Light beige viscous liquid
Coverage at 1 mil (25 micron)	730ft ² /gal (17.9m ² /l)
Dry Film thickness (per coat)	2.0 – 2.5 mils (50 – 62.5 microns)
pH	9.0-9.9 (neat)
Non-volatile content	42-48%
Solids by volume	44-47%
Viscosity	100-1000 cps
Density	8.4 – 8.6 lb/gal (1.00 – 1.03kg/l)
Dry to touch time	30-45 min at 75°F (24°C)
Dry to re-coat time	1-2 hr at 75°F (24°C)
VOC (ASTM D-3960)	0.75 lb/gal (.89kg/l)

Test Data

Humidity chamber (ASTM D-1748)	500 hr
Outdoor Exposure (2 coats)	1500 + hr

PACKAGING AND STORAGE

CorShield VpCI Strippable Coating is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums. CorShield VpCI Strippable Coating should be stored in a

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Distributed by:



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.CortecVCI.com>

printed on recycled paper  100% post consumer

Revised 5/06/08. ©Cortec Corporation 2002-2008. All rights reserved. Supersedes: 3/11/02.
Cortec®, VpCI™, and CorShield® are trademarks of Cortec Corporation. © 2008, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.

ECORR Systems
a Division of Root International, Inc.
24650 State Road 54
Lutz, FL 33559

sales@ecorrystems.com
www.ecorrystems.com

Tel: 866-830-4050
Fax: 813-264-1975