



HIGH PERFORMANCE VpCI PACKAGING

Cor-Pak® VpCI™ Cocooning Stretch Film



Note: ID and OD handling protection are integral components of the cocooning packaging system. For more information regarding this packaging system, contact Cortec Corporation.

FEATURES

- Designed specifically for cocooning system
- Cortec® VpCI™ corrosion protection
- Low cost packaging system
- Mechanized system
- Eliminates steel strapping
- See through packaging
- Assures ready product
- Customer satisfaction

BENEFITS

- Superior toughness and pliability to conform to coil configuration
- Multi-metal protection for all surfaces
- Minimal equipment investment with substantial reduction in labor costs
- Increased production through-put
- Eliminates cost and associated problems
- Visual inspection for inventory and shipping control
- Clean corrosion free dry product possible
- Easy application, removal and recyclable

PACKAGING AND STORAGE

Cor-Pak® VpCI™ Cocooning Stretch film is available in 20" (50 cm) and 30" (76 cm) widths with a thickness of 2-mils (50 microns). Call Cortec Customer Service for custom size requirements.

DESCRIPTION

Cor-Pak® VpCI™ Cocooning Stretch film is designed specifically for applications requiring a strong but pliable film to conform to products of circular configuration such as primary metal coils. It is being used effectively in a new low cost wrapping system to package cold rolled and galvanized steel coils as well as large aluminum coils. These primary metal coils are wrapped in rolling position with the bore or eye horizontal by the so called "cocooning" method.

With Cortec® patented VpCI™ technology providing multi-metal corrosion protection, all surfaces of the metal is protected with a monomolecular layer of vapor phase corrosion inhibitors.

This unique stretch film maintains the same high performance strength and holding force of standard Cor-Pak® VpCI™ Stretch Film. Additionally, it conforms exceptionally well to the curvature of coils with cling properties designed to prevent slippage and zippering. Cor-Pak® VpCI™ Cocooning Stretch Film makes mechanization by the "cocooning" method possible for a most cost effective packaging system while improving package integrity and appearance. As with all Cortec films, the product is environmentally friendly and fully recyclable.



Cor-Pak® VpCI™ Cocooning Stretch film should be stored indoors at room temperature, sealed in its original packaging.

PHYSICAL PROPERTIES

Physical Properties Analysis (2-mil film)

Test Method	Direction*	Cor-Pak® Cocooning Film
ASTM D 882-91 (Tensile Strength @ break, psi)	MD TD	3341.4 4314.8
ASTM D 882-91 (Elongation @ break, %)	MD TD	766.0 784.8
ASTM 1922-92 (Elmendorf Tear Strength, gf)	MD TD	1370.8 2773.3
ASTM 3420-95 (Impact Strength, g/mil)	-	834.8

*MD - Machine Direction TD - Transverse Direction

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet http://www.cortecvci.com

Distributed by:

ECORR Systems
 a Division of Root International, Inc.
 24650 State Road 54
 Lutz, FL 33559

printed on recycled paper 10% post consumer
 Revised 8/20/01. Cortec Corporation 2001. All rights reserved. Supersedes: 7/12/01.



Certificate No.70781

Certificate No.81867

sales@ecorrystems.com
 www.ecorrystems.com

Tel: 866-830-4050
 Fax: 813-264-1975